



LED Industrial Light

**CE & RoHS Certified LED Floodlight Light in Industrial Area.
Tank Series**

CE RoHS

www.khjled.com



Features And Benefits:

- High efficacy LED Source with long lifespan, L70 > 100,000 hours @ 25°C ambient
- 5-year performance warranty
- Low THD around 10%, Less interference
- 6KV Surge Protection
- Robust aluminium housing and strong tempered glass
- Vibration and shock resistant
- Low maintenance
- Dust proof structure design to avoid dust accumulation

Applications:



Cement plants



Warehouse



Factory



Power Generation



Power Transmission



Shipping industry

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

LED Floodlight

Standard & Certificate:

Certificate:	• CE • RoHS
Executive Standard:	• EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 • EN 60598-1, EN 60598-2-5, EN 62031, EN 62493 • IEC 62321-4, IEC 62321-5, IEC 62321-6 • IEC 62321-7-1, IEC 62321-7-2, IEC 62321-8

Electrical & Photometric Features:

Luminaire Efficacy:	Max:152lm/W
Lifespan:	>100,000 hours
Operating Voltage:	100-277 VAC,141-392VDC(347-480 VAC,491-679 VDC are optional)
Power:	80W/100W/120W(Single lamp),160W/200W/240W(Two lamps), 320W/400W/480W(Four lamps)
Frequency:	50/60Hz
Power Factor:	> 0.98
THD:	< 10%
CRI:	> 70
Insulation Class:	I
Surge Protection:	4KV/6KV
LED Driver:	Over voltage protection/short circuit protection


Mechanical Features:

Weight:	6.3Kg(80W~120W)/13Kg(160W~240W)/28kg(320W~480W)
Size:	332*212*100mm(80W~120W)/332*426*100mm(160W~240W) 671*426*100mm(320W~480W)
Ambient Temperature:	-40℃-+55℃
Earthing Protection:	M4 (external earth bolts)
IP Code:	IP66
Enclosure Material:	Aluminium
Enclosure Colour:	Grey RAL7040
Coating:	Epoxy powder coating
Exposed Fastener:	Stainless steel
Protective Cover:	Tempered glass,Stand 7J impact

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

Production Definition



Ordering information

P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	Color Temp.	CCT(K)
KTK80**CH-E	100-277 VAC (141-392 VDC)	12107	80	Cool white	5700K±300K
KTK80**NH-E		12107		Natural white	5000K±300K
KTK80**NH-E		12107		Natural white	4000±300k
KTK80**WM-E		10896		Warm white	3000±300k
KTK100**CH-E		14954	100	Cool white	5700±300k
KTK100**NH-E		14954		Natural white	5000±300k
KTK100**NH-E		14954		Natural white	4000±300k
KTK100**WM-E		13458		Warm white	3000±300k
KTK120**CH-E		17310	120	Cool white	5700±300k
KTK120**NH-E		17310		Natural white	5000±300k
KTK120**NH-E		17310		Natural white	4000±300k
KTK120**WM-E		15579		Warm white	3000±300k
KTK160**CH-S2-E		22910	160	Cool white	5700K±300K
KTK160**NH-S2-E		22910		Natural white	5000K±300K
KTK160**NH-S2-E		22910		Natural white	4000±300k
KTK160**WM-S2-E		20619		Warm white	3000±300k
KTK200**CH-S2-E		29145	200	Cool white	5700±300k
KTK200**NH-S2-E		29145		Natural white	5000±300k
KTK200**NH-S2-E		29145		Natural white	4000±300k
KTK200**WM-S2-E		26230		Warm white	3000±300k
KTK240**CH-S2-E		34136	240	Cool white	5700±300k
KTK240**NH-S2-E		34136		Natural white	5000±300k
KTK240**NH-S2-E		34136		Natural white	4000±300k
KTK240**WM-S2-E		30884		Warm white	3000±300k

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.


P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	Color Temp.	CCT(K)
KTk320**CH-S4-E	100-277 VAC (141-392 VDC)	46400	320	Cool white	5700±300k
KTk320**NH-S4-E		46400		Natural white	5000±300k
KTk320**NH-S4-E		46400		Natural white	4000±300k
KTk320**WM-S4-E		41760		Warm white	3000±300k
KTk400**CH-S4-E		58054	400	Cool white	5700±300k
KTk400**NH-S4-E		58054		Natural white	5000±300k
KTk400**NH-S4-E		58054		Natural white	4000±300k
KTk400**WM-S4-E		52248		Warm white	3000±300k
KTk480**CH-S4-E		69120	480	Cool white	5700±300k
KTk480**NH-S4-E		69120		Natural white	5000±300k
KTk480**NH-S4-E		69120		Natural white	4000±300k
KTk480**WM-S4-E		62208		Warm white	3000±300k

Remarks: 1.The first * stands for Operating Voltage including default -100-277VAC,D-347-480VAC .
2.The second * stands for Candela Distribution including H3V3,H5V5,H6V6.


CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.


Candela Distribution



H3V3(40°)/High efficacy LED Source



H5V5(80°)/High efficacy LED Source



H6V6(120°)/High efficacy LED Source



CE RoHS


CE & RoHS Certified LED Floodlight in Industrial Area.

Installation Method

Stanchion mount / Wall mount

(unit:mm)


360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-SUS316

Single lamp


360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-2-SUS316

Two lamps

360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-4-G

Four lamps

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

Optional Parts

No.	Installation Accessories	Part No.	Picture	Material	Weight(Kg)	QTY	Remarks
1	Stanchion Bracket	SBT-TK-SUS316		SUS316	0.8	1	Single lamp
2	Stanchion Bracket	SBT-TK-2-SUS316		SUS316	1	1	Two lamps
3	Stanchion Bracket	SBT-TK-4-G		Q235	3	1	Four lamps
4	Safety Chain	SSR-TK1-SUS304		SUS304	0.06	1	Single lamp 0.8m
						2	Four lamps 0.8m
		SSR-TK2-SUS304				1	Two lamps 0.8m